

GO-4 XTR GAS REFUSE - SPECIFICATIONS

MOTOR

66 h.p., liquid cooled, 3-cylinder, overhead cam, 4-cycle, electronically fuel injected, ultra efficient 1.0L with EGR clean burning emissions control.

TRANSMISSION

4-speed automatic
(automotive transaxle with electronically controlled shift)

DIMENSIONS

72" Overall Height with Cab
147" Overall Length
57" Overall Width
22 Foot Outside Turning Diameter
11 Foot Turning Radius
95" Wheelbase

BRAKING

Hydraulic Disc Brakes on all Three Wheels
With Dual Master Cylinder
Parking – Hydraulic over Mechanical

ELECTRICAL SYSTEM

Charging – Heavy Duty automotive alternator
DOT approved LED headlights
DOT Approved LED Stop / Tail and Turn Lights
DOT Approved High Visibility Stop Light
Starting – 12-volt starting motor.
Interlock prevents starter from operating unless shift lever is in park or neutral.
Gauges – LCD Digital Display
Speed, Odometer, Hour Meter, Warning Message, Fuel Level, Oil pressure warning, three stage water temperature light (blue / still cold, red/ running too hot, off / normal temp)
Wiring – Pre Wired for Radio and Municipal Lighting(Optional)

SPEED

Electronically Limited to a Maximum of 30 mph

COLOR

White Body Panels and Black Chassis

FUEL TANK AND MILEAGE

9 US Gallon Tank, up to 40-45 MPG (based on factory testing and CARB testing, excludes constant idle time and high payloads)

SUSPENSION

Front – Leading Link Suspension
Polyurethane Isolation System
Rear – Independent McPherson Strut with fortified bracketry for higher payload

CLIMATE CONTROL

Liquid Core 20000 BTU Heater(Optional)
Air Conditioning (Optional)

STEERING

Adjustable Tilt Steering Wheel
with Center Mounted Horn

TIRES

165/60 14" All season Radial on front, Rear 2-13 or 14"
High load index Tires w Steel Rim(Check for details)

STRUCTURE

3-Wheel Platform with Ultra Tough Heavy Duty 2.5" Rollbar Chassis
White Aluminum and Plastic Body Panels
1.75 Cub YD Heavy Duty Poly Bin with Fortified Steel Structure and Hydraulic Pump
Hinged Door (Optional), Steel Front and Rear bumpers, Exterior Nerf Bars(Optional – if no doors added, front nerf is required)

FEATURES

Two Outside Rear View Mirror
Rear View Back Up Camera
Electric Windshield Wiper with Intermittent Control And Windshield Washer
Inside Cab Ceiling Light(Optional)
Floor Mat
12 V DC Accessory Port
LTA (Lateral thrust alarm)

SEAT

One Passenger Adjustable Forwards/Backwards, Recline, Leatherette material
3 Point Shoulder Harness Seat Belts

WEIGHT CAPACITY

Vehicle Weight with Bin– 1900 Pounds –Base,no Option
Rated Total Payload Capacity, 1000lbs w/ Operator

WARRANTY

One Year Full Warranty on Manufacture Defects
Technician Travel Time Excluded

OPTIONS

Please Inquire for Full Listing