



KB-2 SERIES



**CDL
Exempt**

KBF-2 with TKB-1820 Body

Boom:

- ☆ 17' Fixed Boom
- ☆ 1 Piece Main Boom
- ☆ 270° Rotation
- ☆ Swing Controls

Body:

- ☆ 20 Cu. Yd. Capacity
- ☆ 1 Piece 3/16" Floor
- ☆ 8" Main Sill
- ☆ 4" Joists on 12" Centers

Grapple/Bucket:

- ☆ 360 Continuous Rotation
- ☆ 2,000 lbs Clamping Force
- ☆ Replaceable Cutting Edges



All design, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for informational purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with conditions encountered. The only warranty is our standard written warranty for this product at time of shipment.

HOL-MAC CORPORATION • P.O. Box 349 • Bay Springs, MS 39422 • (601) 764-4121



www.e-pac-mac.com

REFUSE AND RECYCLING EQUIPMENT

TECHNICAL DATA AND SPECIFICATIONS

GENERAL SPECIFICATIONS:

Height of boom to ground in lowest travel position.....	10 ft.
Boom Length (Fixed).....	17 ft.
Body Length.....	18 ft.
Body Capacity.....	20 cu yds
Weight of loader, body and truck (empty).....	18,800 lbs
Outrigger extended.....	9.5 ft.
retracted.....	7 ft.
Body hoist capacity.....	30,000 lbs

GRAPPLE/BUCKET:

360° continuous rotation	
Width.....	3 ft.
(Optional: 2 ft.)	
Fully open.....	4 ft.
High strength tempered steel replaceable cutting edges	

BODY:

Length.....	18 ft.
Capacity.....	20 cu yds
Tilt to 45° for dumping	
Two heavy-duty "barn type" doors	
Floor- 1 piece 3/16 inch smooth steel plate	
Sides- 10 gauge smooth steel plate	

RECOMMENDED CHASSIS:

Cab to axle (minimum).....	168 inches
After Frame (minimum).....	90 inches
Clear Frame.....	37 inches
Front axle	10,000 lbs
Rear Axle	16,000 lbs
GVW	25,999 lbs
Engine (minimum).....	210 HP
Frame.....	1,100,000 RBM



Low profile pedestal with "A-Frame" outriggers. The outriggers extend to a width of 9 ½ feet.



The boom is equipped with a continuous rotating grapple. The grapple is constructed with bolt-on heat-treated steel cutting edges for ease of replacement. The edges are overlapping to prevent scalping. The bucket is 36" wide with a 48" opening from lip to lip.



Controls swing from side to side for operator requirements. Optional dual controls available.



The boom is a 17 foot fixed boom constructed with a one piece main boom.

DISTRIBUTED BY



All design, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for information purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with conditions encountered. The only warranty is our standard written warranty for this product at time of shipment.

HOL-MAC CORPORATION • P.O. Box 349 • Bay Springs, MS 39422 • (601) 764-4121

www.e-pac-mac.com

REFUSE AND RECYCLING EQUIPMENT