

KBF-20H-RO with TKB-1824 Body

A FIVE-STAR RATING PLACES THE **KB-20 SERIES** IN A CLASS OF ITS OWN.



- **★** QUALITY
- **★** SAFE
- **★** ECONOMICAL
- **★** USER-FRIENDLY
- **★** DURABLE



All design, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for information purposes only and shall not be constructed to warrant suitability of the unit for any particular purpose, as performance may vary with conditions encountered. The only warranty is our standard written warranty for this product at time of shipment.

HOL-MAC CORPORATION • P.O. Box 349 • Bay Springs, MS 39422 • (601) 764-4121



www.e-pac-mac.com

TECHNICAL DATA AND SPECIFICATIONS

BUCKET:

BODY:

| 360° continuous rotation. | (Optional 270°) |
|---------------------------|------------------|
| Width | 4 ft. |
| Fully open | 5 ft. |
| High strength tempered s | teel replaceable |
| cutting edges. | |

| Length18, 19 & 20 ft. |
|--------------------------------------|
| Capacity 20, 24, 25, or 30 cu. Yds. |
| Two heavy-duty "barn type" doors |
| Floor – 3/16 inch smooth steel plate |
| Sides – 10 gauge smooth steel plate |

GENERAL SPECIFICATIONS:

| Height of boom to ground in the lowest travel position | 11 ft. |
|--|--------|
| Boom length (16 ft. with 4 ft. extension) | |
| Lifting capacity at 20 feet (with grapple) | |
| Outrigger: Extended | |
| Retracted | |





DISTRIBUTED BY



All design, specifications and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for information purposes only and shall not be constructed to warrant suitability of the unit for any particular purpose, as performance may vary with conditions encountered. The only warranty is our standard written warranty for this product at time of shipment.

HOL-MAC CORPORATION • P.O. Box 349 • Bay Springs, MS 39422 • (601) 764-4121

www.e-pac-mac.com