"Compared to other compressors, this one has done the job and then some. I highly recommend it. I filled up a 375 x 39 to 100 psi in 15 minutes."

"These [digital control features] have solved cold weather startup problems our customers have had with other compressors. The standby mode takes a load off the hydraulic system when air is not being used. This is a great feature compared to the competition...I would recommend this compressor to all construction contractors."

- Kal Tire Vernon, BC

- Wilcox Bodies Milton, ON





PH 250-740-3200 FX 250-740-3201 TF 1-800-738-8622

1333 Kipp Road Nanaimo, BC, V9X 1R3 CANADA www.vmacair.com





PREDATAIR Hydraulic-Driven Air Compressors

COMPACT. POWERFUL™

1-800-738-8622

www.vmacair.com

ADVANCED TECHNOLOGY ON-DEMAND

Advanced digital technology allows you to reduce fuel consumption and heat generation in Standby Mode – the revolutionary feature that puts the compressor to rest when there is no demand for air. The VMAC PREDATAIR wakes immediately when air is required again. Equipped with a remote digital LCD control unit, operators can now monitor hydraulic and compressor oil temperature,

compressor pressure, system hours and perform on-the-spot analysis in less than 60 seconds. Settings are adjustable to suit the operators' needs. The automated control module protects the system from operator error. Built in freeze protection and an over-temp safety sensor also protect the VMAC PREDATAIR when operating in extreme climates.



VMAC has utilized experience and technology gained from over 20 years in the underhood air compressor business to design the smallest and lightest hydraulic compressors in their CFM class. The compact size and weight of the VMAC PREDATAIR reduces wear and tear, delivers fuel savings and maximizes the amount of space on your work truck. Maintenance on the VMAC PREDATAIR can be done easily and quickly, with easy-to-access serviceable parts.

COMMON TOOLS AIR REQUIRED 1"IMPACT GUN 30 - 50 CFM 12 - 35 CFM 3/8" - 5/8" DRILL 60LB PAVING BREAKER 12 - 48 CFM 4" HORIZONTAL GRINDER 20 - 60 CFM

The VMAC Rotary Screw Compressor delivers air on-demand up to 100% duty cycle and packs the muscle to power up to a 60LB jackhammer or a 1" impact wrench. VMAC stands behind its products. North American VMAC Dealer surveys consistently rank VMAC as a top supplier delivering prompt and professional customer and technical support. A full 2 year warranty comes standard on every VMAC air system.


- AIR ON-DEMAND, 100% DUTY CYCLE
- UP TO 40 OR 60 CFM

- COLD START PROTECTION



SPECIFICATIONS*

PERFORMANCE CHARACTERISTICS	PREDATAIR40	PREDATAIR60
Rated Air Capacity - CFM (m³/min)	25-40 (0.71-1.13)	40-60 (1.13-1.70)
Pressure Range – PSI (kPa)	Up to 150 (1,034)	Up to 150 (1,034)
1 1 0 0 0 al o 1 al qui a y	Sp to 100 (1/00 1/	
DIMENSIONS		
in	16.5 (w) x 24.0 (l) x 18.0 (h)	16.5 (w) x 24.0 (l) x 18.0 (h)
cm	42 (w) x 61 (l) x 46 (h)	42 (w) x 61 (l) x 46 (h)
WEIGHT		
Dry Weight – Ib (kg)	150 (68)	160 (72.5)
Working Weight – Ib (kg)	162 (74)	172 (78.5)
HYDRAULIC SPECIFICATIONS	0.14/25 52\	14 21 /52 90\
Hydraulic Flow Required GPM (L/min)	9-14 (35-53)	14-21 (53-80)
Hydraulic Pressure @ Full Load PSI (bar)	2,350 (162)	2,275 (157)
COMPRESSOR		
Туре	Direct drive, rotary screw	Direct drive, rotary screw
Discharge Air Outlet Size	3/4 NPT	3/4 NPT
Oil Capacity - gal (L)	1.1 (4)	1.1 (4)
HYDRAULIC CONNECTIONS		
Inlet	#12 ORB	#12 ORB
Outlet	#16 ORB	#16 ORB
Case Drain (Factory Plumbing To Return Line)	#4 ORB	#4 ORB
Electrical Input	20A @ 12V (nominal) - 30A fuse or breaker	20A @ 12V (nominal) - 30A fuse or breaker
WARRANTY	2 years	2 years
SAFETY FEATURES		
High Temperature Shutdown	Yes	Yes
Cold Start Protection	Yes	Yes
200 PSI Air Pressure Relief Valve	Yes	Yes
Automatic Air Pressure Blowdown	Yes	Yes
Air System One Way Check Valve	Yes	Yes
2,800 PSI Hydraulic Pressure Relief Valve Setting	Yes	Yes
- 2,000 1 31 Hydraulic 1 ressure Heller valve Setting		100



^{*} FOR MORE SPECIFICATION DETAILS PLEASE CALL OUR TECHNICAL SUPPORT DEPARTMENT AT 1-888-241-2289

PRED60 100 PSI

PRED60 125 PSI

PRED60 150 PSI